

DuraGem™ LED Linear High Bay

The DuraGem™ LED Linear High Bay, 130 lm/W, IP40 Dry Location, 0-10V Dimmable, Premium Indoor Luminaire, Smart Sensor Ready.

Illuminate indoor facilities day and night with DuraGem™ engineering. 2-FT and 4-FT luminaires available. Smart Sensor Ready for daylight, bi-level dimming, and motion detection.

Project:
Date:
Catalog No:
Prepared By:

2-FT and 4-FT Models



Industry Standard Design



FEATURES

Lumen Output	11700 to 41730 lumens
Efficacy	130 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	4000K or 5000K
IP Rating	IP40 Dry Location
Size	2-FT, 4-FT
Warranty	7 Years

APPLICATIONS

Premium indoor luminaire for hanging or pendant mounting in high ceiling spaces above 25 feet. Suitable for gymnasiums, warehouses, manufacturing, packaging, storage, aisles, and covered decks.

CONSTRUCTION

Manufactured for durability using aluminum sheet housing with semi-gloss coating to resist corrosion, discoloration, and scratching. Ventilated driver bay for additional heat dissipation. IP40 Dry Location rated for protection against solid objects 1.0mm diameter and greater, dry location: IEC 60529.

ELECTRICAL

Input voltage 120-277V models with 0-10V Continuous Dimming. Operating temperatures -4°F to 122°F (-20°C to 50°C).

MOUNTING

Aluminum V-Hooks and Chains for hanging standard. Optional Pendant Mount Bracket available.

OPTICS

Anti-UV Frosted Polycarbonate Lens standard. Protective Wire Guards available.

CONTROLS

Fixture mounted daylight, bi-level dimming, and motion detection sensor available.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant.

WARRANTY

7 year exclusive limited warranty. View complete product warranty information <https://etheriumled.com/warranty/>.

CORRELATED COLOR TEMPERATURES (CCT)

4000K

5000K

