

## DuraGem™ LED Troffer

The DuraGem™ LED Troffer, 130 lm/W, 0-10V Dimmable, Premium Indoor Luminaire, Smart Sensor Ready.

Illuminate indoor facilities day and night with DuraGem™ engineering. 2x2, 1x4 and 2x4 luminaires available.

Project:
Date:
Catalog No:
Prepared By:



2x2, 1x4 and 2x4 Models



### CORRELATED COLOR TEMPERATURES (CCT)

4000K

5000K



### FEATURES

<b>Lumen Output</b>	2990 to 5850 lumens
<b>Efficacy</b>	130 lm/W
<b>Input Voltage</b>	120-277V
<b>Dimmable</b>	0-10V Continuous
<b>CCT</b>	4000K or 5000K
<b>Size</b>	2x2, 1x4, 2x4
<b>Warranty</b>	7 Years

### APPLICATIONS

Premium indoor luminaire suitable for general indoor commercial spaces, lobbies, offices, meeting rooms, schools, retail stores, restrooms, hallways, and work-stations.

### CONSTRUCTION

Manufactured for durability using aluminum sheet housing with satin coating to resist corrosion, discoloration, and scratching. For use in Dry Locations.

### ELECTRICAL

Input voltages 120-277V with 0-10V Continuous Dimming. Operating temperatures -4°F to 104°F (-20°C to 40°C).

### MOUNTING

Recessed T-Bar Ceiling Mount.

### OPTICS

Anti-UV Frosted Polycarbonate Lens.

### LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant.

### WARRANTY

7 year exclusive limited warranty. View complete product warranty information <https://etheriumled.com/warranty/>.

## SPECIFICATIONS

### ENERGY DATA

**Input Voltage:** 120-277V

**Input Frequency:** 50/60 Hz

**Wattage:** 23W, 25W, 30W, 34W, 45W

**Power Factor:** >0.9

**Total Harmonic Distortion (THD):** <10%

**Operating Temperature:** -4°F to 104°F (-20°C to 40°C)

### LIGHTING DATA

**Lumens:** 2990 (23W), 3250 (25W), 3900 (30W), 4420 (34W), 5850 (45W)

**Lumens Per Watt:** 130 lm/W

**Color Correlated Temperature (CCT):** 4000K, 5000K

**Dimmable:** 0-10V

**Color Rendering Index (CRI):** >83

**L70:** 75000 hours