

DuraGem™ LED Wraparound

The DuraGem™ LED Wraparound, 130 lm/W, 0-10V Dimmable, Premium Indoor Luminaire, Smart Sensor Ready.

Illuminate indoor facilities day and night with DuraGem™ engineering. 2-FT and 4-FT luminaires available. Smart Sensor Ready for daylight, bi-level dimming, and motion detection.

Project:
Date:
Catalog No:
Prepared By:

2-FT and 4-FT Models



FEATURES

Lumen Output	3250 to 5200 lumens
Efficacy	130 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	4000K or 5000K
Size	2-FT, 4-FT
Warranty	7 Years

APPLICATIONS

Premium indoor luminaire suitable for general indoors, lobbies, offices, meeting rooms, restrooms, hallways, stairwells, storage-closets, kitchens, and work-stations.

CONSTRUCTION

Manufactured for durability using aluminum sheet housing with semi-gloss coating to resist corrosion, discoloration, and scratching. For use in Dry Locations.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Operating temperatures -4°F to 122°F (-20°C to 50°C).

MOUNTING

Surface Mounting on ceilings or beams.

OPTICS

Anti-UV Frosted Prismatic Polycarbonate Lens.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant.



WARRANTY

7 year exclusive limited warranty. View complete product warranty information <https://etheriumled.com/warranty/>.

CORRELATED COLOR TEMPERATURES (CCT)

4000K

5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V

Input Frequency: 50/60 Hz

Wattage: 22W, 25W, 40W

Power Factor: >0.9

Total Harmonic Distortion (THD): <10%

Operating Temperature: -4°F to 122°F (-20°C to 50°C)

LIGHTING DATA

Lumens: 2860 (22W), 3250 (25W), 5200 (40W)

Lumens Per Watt: 130 lm/W

Color Correlated Temperature (CCT): 4000K, 5000K

Dimmable: 0-10V

Color Rendering Index (CRI): >82

L70: 75000 hours